

AP-125 SERIES

Full IP69K Stainless Touch IPC

Features

Intel® Mobile 13th Core™ i5-1345URE WT
Fanless solution and compact housing
DDR5 5200 MHz SODIMM Slot up to 32GB
Full IP69K Stainless design
All M12 waterproof connectors
Display Size: 15" / 17" / 19" / 21.5" / 24"
DC-in 12~24V
True flat PCT / 5 wires resistive
Yoke Mount / VESA Mount
Wide operating temperature supported



Specifications

Display for 4:3 Ratio				Display for 16:9 Ratio			
Size	15" TFT	17" TFT	19" TFT	21.5" TFT	24" TFT		
Resolution	1024 x 768	1280 x 1024	1280 x 1024	1920*1080	1920*1080		
Colors	16.7M	16.7M	16.7M	16.7M	16.7M		
Luminance	300 cd/m2	350 cd/m2	250 cd/m2	250 cd/m2	250 cd/m2		
Contrast Ratio	2500:1	1000:1	1000 : 1	3000 : 1	1000 : 1		
View Angle (H/V)	176°/176°	170°/160°	170°/160°	176°/176°	170°/160°		
SYSTEM							
CPU	Intel® Mobile 13th Core™ i5-1345URE WT						
Memory	Single-channel DDR5 5200 MHz Up to 32 GB						
Storage	1 x SATA 3.0						
OS Support	Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2)			Linux (Support by request)			
	Windows 11 IoT Enterprise (64-bit, 23H2, Pre-scan)						
I/O Ports	* The I/O interface shown may vary depending on the selected motherboard.						
M12 RS232	2			M12 GLAN	2		
M12 USB 2.0	2						
Expansion Slot							
M.2	1 x M.2 M key (PCIe Gen4 x4 NVMe), 2280						
	1 x M.2 B key (PCIe x1, USB 2.0, w/NANO SIM-Holder), 2242/3042						
	1 x M.2 E key (PCIe x1, USB 2.0, w/CNVi), 2230						
MECHANICAL & ENVIRONMENTAL							
Operation Temp.	-40 ~ 70°C						
Storage Humidity	10 ~ 90%, non-condensing						
Form Factor							
Touch Screen	True flat PCT / 5 wires resistive						
Mounting	Yoke Mount / VESA Mount						
Power Supply	Full IP67 Waterproof Power Adapter: 12V/24V default; 9~36V input supported. Customization by customer.						
Optional							
Panel Type	High Brightness LCD Panel: Available in various sizes and brightness specifications. Please inquire for available options and custom configurations						
WIFI	External Antenna (Wi-Fi): Supports M.2 Wi-Fi module with external antenna connection for enhanced signal performance						
Power adaptor	Full IP67 Waterproof Power adaptor : Specifications may vary by country (150W / 100 ~ 305V AC input / 12V DC output) / (150W / 100 ~ 305V AC input / 24V DC output)						

