

BB-110 SERIES

Features

Intel® Celeron® Processor J6412
DDR4 3200MHz SODIMM slots up to 32GB
1 x DP , 1 x HDMI , 2 x GLAN , 4 x USB , 1 x Audio
1 x M key(SATA)2242 , 1 x B key 2242/3042 , 1 x E key 2230
Fanless solution and compact design
Wall mount installation
DC-in 12V/19V/24V
IIoT gateway
Support Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2)



Specifications

SYSTEM	
CPU	Intel® Celeron® Processor J6412, QC, 10W
Memory	2 x SO-DIMMs DDR4 3200 MHz Up to 32 GB
Storage	1 x SATA 3.0
OS Support	Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2) Linux (Support by request)
TPM	Infineon SLB9672VU 2.0
I/O Ports	
RS232/422/485	2 (COM1 、COM2) Optional
RS232	4 (COM3~6) Optional
HDMI	1
DP	1
GLAN	2
USB 2.0	1
USB3.2 Gen2	3
AUDIO	1
Expansion Slot	
M.2	1 x M key 2242 (SATA) 1 x B key 2242 / 3042 (PCIe x1, USB 3.2 Gen 1 x 1, USB 2.0 w / NANO SIM-Holder) 1 x E key 2230 (PCIe x1, USB 2.0) WiFi optional
MECHANICAL & ENVIRONMENTAL	
Operation Temp.	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Form Factor	
Mounting	Wall mount
Power Supply	3 Pin Power Terminal Block for DC-in 12V/19V/24V

