

21.5" 24" Celeron® J6412

Full IP65 Stainless Touch IPC

Features

Fanless and rugged design
 Intel® Elkhart Lake SoC Processors J6412
 True Flat PCT / 5 Wires Resistive touch solution
 Full 304 IP65 6 sides stainless chassis
 All IP65 M12 waterproof connectors
 2 x USB, 2 x RS232, 2 x GLAN
 VESA mount & Yoke mount



Specifications

Display for 16:9 Ratio			
Size	21.5" TFT		24" TFT
Resolution	1920*1080		1920*1080
Colors	16.7M		16.7M
Luminance	250 cd/m2		250 cd/m2
Contrast Ratio	3000 : 1		1000 : 1
View Angle	176°/176°		170°/160°
Model NO.	IP215R112S	IP240R112S	
SYSTEM			
CPU	Intel® Elkhart Lake SoC Processors J6412		
Memory	2 x 260-pin DDR4 3200MHz SODIMM up to 32 GB (16GB per DIMM)		
Storage	1 x SATA 3.0 /1 x M.2 (Key M, 3042/3060/2280) with PCIe x1 for SSD		
OS Support	Windows 10 Pro / Windows 10 IoT Windows 11 Pro / Windows 11 IoT		
TPM	TPM 2.0 onboard IC		
I/O Ports	* The I/O interface shown may vary depending on the selected motherboard.		
M12 RS232	2	M12 USB 2.0	2
M12 GLAN	2		
Expansion Slot			
M.2	1 x M.2 (Key E, 2230) with PCIe x1 and USB 2.0 / WiFi optional 1 x M.2 (Key B, 3042 / 3052) with PCIe x1 / USB 3.2 and USB 2.0 and SIM for 4G/5G		
MECHANICAL & ENVIRONMENTAL			
Operation	0 ~ 45°C		
Storage	10 ~ 90%, non-condensing		
Form Factor			
Touch Screen	15"/17"/19" : PCT / 5W (Single touch) 12"/15"/17"/19"/21.5"/24" : Projected Capacitive Multi-Touch Panel		
Mounting	VESA mount (100 x 100mm) & Yoke mount		
Power Supply	M12 DC-in 9V~36V		

