

OP-121 SERIES

Open Frame Touch IPC

Features

Intel® Mobile 13th Core™ i5-1345UE
Fanless solution and compact housing
DDR5 5200 MHz SODIMM Slot up to 32GB
Display Size: 10.1" / 12.1" / 15" / 15.6" / 17" / 17.3" / 18.5" / 19" / 21.5" / 24"
DC-in 12~24V
True flat PCT / 5 wires resistive / no touch screen
Open frame mount



Specifications

Display for 4:3 Ratio							
Size	10.1" TFT	12.1" TFT	15" TFT	17" TFT	19" TFT		
Resolution	1280 x 800	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024		
Colors	16.7M	16.7M	16.7M	16.7M	16.7M		
Luminance	500 cd/m2	350 cd/m2	300 cd/m2	350 cd/m2	250 cd/m2		
Contrast Ratio	800:1	800:1	2500:1	1000:1	1000 : 1		
View Angle (H/V)	170°/170°	160°/160°	176°/176°	170°/160°	170°/160°		
Display for 16:9 Ratio							
Size	15.6" TFT		17.3" TFT	18.5" TFT		21.5" TFT	24" TFT
Resolution	1366 x 768	1920 x 1080	1920*1080	1366 x 768	1920*1080	1920*1080	1920*1080
Colors	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M
Luminance	400 cd/m2	400 cd/m2	400 cd/m ²	250 cd/m ²	350 cd/m ²	250 cd/m2	250 cd/m2
Contrast Ratio	500 : 1	700 : 1	600 : 1	1000 : 1	1000 : 1	3000 : 1	1000 : 1
View Angle (H/V)	170°/160°	160°/140°	160°/140°	170°/160°	178°/178°	176°/176°	170°/160°
SYSTEM							
CPU	Intel® Mobile 13th Core™ i5-1345UE						
Memory	Single-channel DDR5 5200 MHz Up to 32 GB						
Storage	1 x SATA 3.0						
OS Support	Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2)			Linux (Support by request)			
	Windows 11 IoT Enterprise (64-bit, 23H2, Pre-scan)						
I/O Ports	* The I/O interface shown may vary depending on the selected motherboard.						
RS232	2			USB3.2	4		
HDMI	4				GLAN	4	
Expansion Slot							
M.2	1 x M.2 M key (PCIe Gen4 x4 NVMe), 2280						
	1 x M.2 B key (PCIe x1, USB 2.0, w/NANO SIM-Holder), 2242/3042						
	1 x M.2 E key (PCIe x1, USB 2.0, w/CNVi), 2230						
MECHANICAL & ENVIRONMENTAL							
Operation Temp.	0 ~ 45°C						
Storage Humidity	10 ~ 90%, non-condensing						
Form Factor							
Touch Screen	True flat PCT / 5 wires resistive / no touch screen						
Mounting	Open frame mount Installation						
Power Supply	2 or 3 Pin Power Terminal Block for DC-in 12~24V (Varies depending on the model)						

