

21.5" 24" Celeron® J6412

Front IP65 Silver Aluminum Touch IPC

Features

Intel® Celeron® Processor J6412
Dual DDR4 3200MHz SO-DIMM
5 Wires Resistive (single touch)
IP65 Silver aluminum front bezel
6 x USB, 2 x RS232, 2 x GLAN, Audio
VESA mount & Panel mount & Clip mount
DC in 12V / 24V



Specifications

Display for 16:9 Ratio			
Size	21.5" TFT		24" TFT
Resolution	1920*1080		1920*1080
Colors	16.7M		16.7M
Luminance	250 cd/m2		250 cd/m2
Contrast Ratio	3000 : 1		1000 : 1
View Angle	176°/176°		170°/160°
Model NO.	SP215R901S		SP240R901S
SYSTEM			
CPU	Intel® Celeron® Processor J6412		
Memory	2 x DDR4 3200MHz, Dual Channel SO-DIMM, up to 32GB		
Storage	1 x SATA 3.0 / 64GB Emmc		
OS Support	Windows® 11 (64bit)		
	Windows® 10 (64bit)		
	Linux (Support by request)		
TPM	1 x SATA 3.0 / 64GB Emmc		
I/O Ports	* The I/O interface shown may vary depending on the selected motherboard.		
RS232/422/485	1	USB 2.0	3
RS232	1	USB 3.1 Gen 2	3
GLAN	2	AUDIO	1
Expansion Slot			
M.2	1 x M-key 2242/2280 (PCIe Gen.3x2/SATA interface) Support NVME 1 x B-key 3042 (USB3.1/USB2.0 interface) support W/SIM card slot 1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1)		
MECHANICAL & ENVIRONMENTAL			
Operation	0 ~ 45°C		
Storage	10 ~ 90%, non-condensing		
Form Factor			
Touch Screen	5 Wires Resistive (Single touch)		
Mounting	VESA mount (75 X 75 mm) / (100 X 100 mm) & Panel mount & Clip mount		
Power Supply	3 Pin Power Terminal Block for DC-in 12~24V		

