

SP-125 SERIES

Front IP65 Silver Aluminum
Touch IPC

Features

Intel® 13th Gen Raptor Lake-P Embedded/Industrial SKU Series
DDR5 5200 MHz SODIMM Slot up to 32GB
Display Size: 12" / 15" / 15.6" / 17" / 17.3" / 18.5" / 19" / 21.5" / 24"
5 Wires Resistive (single touch)
IP65 Silver aluminum front bezel
4 x USB3.2 Gen2, 2 x RS232, 4 x GLAN, 4 x HDMI
VESA mount & Panel mount & Clip mount
DC-in 12~24V
Wide operating temperature supported



Specifications

Display for 3:4 Ratio

Size	12.1" TFT	15" TFT	17" TFT	19" TFT
Resolution	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024
Colors	16.7M	16.7M	16.7M	16.7M
Luminance	350 cd/m2	300 cd/m2	350 cd/m2	250 cd/m2
Contrast Ratio	800:1	2500:1	1000:1	1000 : 1
View Angle (H/V)	160°/160°	176°/176°	170°/160°	170°/160°

Display for 16:9 Ratio

Size	15.6" TFT	17.3" TFT	18.5" TFT	21.5" TFT	24" TFT
Resolution	1366 x 768	1920 x 1080	1920*1080	1366 x 768	1920*1080
Colors	16.7M	16.7M	16.7M	16.7M	16.7M
Luminance	400 cd/m2	400 cd/m2	400 cd/m ²	250 cd/m ²	350 cd/m ²
Contrast Ratio	500 : 1	700 : 1	600 : 1	1000 : 1	1000 : 1
View Angle (H/V)	170°/160°	160°/140°	160°/140°	170°/160°	178°/178°

SYSTEM

CPU	Intel® Mobile 13th Core™ i5-1345URE, 28W	
Memory	Single-channel DDR5 5200 MHz Up to 32 GB	
Storage	1 x SATA 3.0	
OS Support	Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2) Windows 11 IoT Enterprise (64-bit, 23H2, Pre-scan)	Linux (Support by request)
TPM	Infineon® SLB 9672VU2.0	

I/O Ports

RS232	2	GLAN	4
HDMI	4	USB 3.2 Gen 2	4

Expansion Slot

M.2	1 x M.2 M key (PCIe Gen4 x4 NVMe), 2280 1 x M.2 B key (PCIe x1, USB 2.0, w/NANO SIM-Holder), 2242/3042 1 x M.2 E key (PCIe x1, USB 2.0, w/CNV), 2230
-----	--

MECHANICAL & ENVIRONMENTAL

Operation Temp.	-20 ~ 60°C
Storage Humidity	10 ~ 90%, non-condensing

Form Factor

Touch Screen	5 Wires Resistive (Single touch)
Mounting	VESA mount (75 X 75 mm) / (100 X 100 mm) & Panel mount & Clip mount
Power Supply	3 Pin Power Terminal Block for DC-in 12~24V
WIFI Optional	External Antenna (Wi-Fi): Supports M.2 Wi-Fi module with external antenna connection for enhanced signal performance

