

21.5" 24" CF17 i7 i5 i3 WT

Front IP66/67 Silver Aluminum Touch IPC

Features

Intel® 13th Gen Raptor Lake-P Embedded/Industrial SKU Series

DDR5 5200 MHz SODIMM Slot up to 32GB

4 x HDMI, 4 x GLAN, 4 x USB 3.2 Gen 2, 2 x RS232

Front IP66/67 aluminum Touch IPC

5 Wires Resistive (Single touch) / True Flat PCT

VESA mount / Panel mount / Clip mount

Quadruple independent displays: 4HDMI, 1 LVDS/eDP

Wide operating temperature supported

Wide Voltage DC-IN 12~24V



Specifications

Display for 16:9 Ratio			
Size	21.5" TFT		24" TFT
Resolution	1920*1080		1920*1080
Colors	16.7M		16.7M
Luminance	250 cd/m2		250 cd/m2
Contrast Ratio	3000 : 1		1000 : 1
View Angle	176°/176°		170°/160°
Model NO.	TP215R124W TP215R125W TP215R126W	TP240R124W TP240R125W TP240R126W	
SYSTEM			
CPU	Intel® Mobile 13th Core™ i7-1365URE(124)/i5-1345URE(125)/i3-1315URE(126) , 28W		
Memory	Single-channel DDR5 5200 MHz Up to 32 GB		
Storage	1 x SATA 3.0		
OS Support	Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2)		
	Windows 11 IoT Enterprise (64-bit, 23H2, Pre-scan)		
	Linux (Support by request)		
I/O Ports	* The I/O interface shown may vary depending on the selected motherboard.		
RS232	2	GLAN	4
HDMI	4	USB 3.2 Gen 2	4
Expansion Slot			
M.2	1 x M.2 M key (PCIe Gen4 x4 NVMe), 2280 1 x M.2 B key (PCIe x1, USB 2.0, w/NANO SIM-Holder), 2242/3042 1 x M.2 E key (PCIe x1, USB 2.0, w/CNVi), 2230		
MECHANICAL & ENVIRONMENTAL			
Operation	-20 ~ 60°C		
Storage	10 ~ 90%, non-condensing		
Form Factor			
Touch Screen	15" / 17" / 19" : PCT / 5W (Single touch) 15" / 15.6" / 17" / 19" / 21.5" / 24" : Projected Capacitive Multi-Touch Panel		
Mounting	VESA mount (100x100mm) & Panel mount & Clip mount		
Power Supply	DC-in 12~24V 3P Power terminal block		
WIFI Optional	External Antenna (Wi-Fi): Supports M.2 Wi-Fi module with external antenna connection for enhanced signal performance		

