

WP-123 SERIES

Full IP65 Stainless Touch IPC

Features

Intel® 13th Gen Raptor Lake-P Embedded/Industrial SKU Series

DDR5 5200 MHz SODIMM Slot up to 32GB

Display Size: 15" / 17" / 19" / 21.5" / 24"

2 x M12 RS232, 2 x M12 GLAN, 2 x M12 USB 2.0

Full IP65 Stainless Touch IPC

5 Wires Resistive (Single touch)

VESA mount & Yoke mount

Wide Voltage DC-IN 12~24V (OCP & OVP)



Specifications

Display for 4:3 Ratio			Display for 16:9 Ratio		
Size	15" TFT	17" TFT	19" TFT	21.5" TFT	24" TFT
Resolution	1024 x 768	1280 x 1024	1280 x 1024	1920*1080	1920*1080
Colors	16.7M	16.7M	16.7M	16.7M	16.7M
Luminance	300 cd/m2	350 cd/m2	250 cd/m2	250 cd/m2	250 cd/m2
Contrast Ratio	2500:1	1000:1	1000 : 1	3000 : 1	1000 : 1
View Angle (H/V)	176°/176°	170°/160°	170°/160°	176°/176°	170°/160°
SYSTEM					
CPU	Intel® Mobile 13th Core™ i3-1315UE, 28W				
Memory	Single-channel DDR5 5200 MHz Up to 32 GB				
Storage	1 x SATA 3.0				
OS Support	Windows 10 IoT Enterprise 2021 LTSC (64-bit, 21H2) Windows 11 IoT Enterprise (64-bit, 23H2, Pre-scan)			Linux (Support by request)	
I/O Ports	* The I/O interface shown may vary depending on the selected motherboard.				
M12 RS232	2			M12 USB 2.0	2
M12 GLAN	2				
Expansion Slot					
M.2	1 x M.2 M key (PCIe Gen4 x4 NVMe), 2280 1 x M.2 B key (PCIe x1, USB 2.0, w/NANO SIM-Holder), 2242/3042 1 x M.2 E key (PCIe x1, USB 2.0, w/CNVi), 2230				
MECHANICAL & ENVIRONMENTAL					
Operation Temp.	0 ~ 45°C				
Storage Humidity	10 ~ 90%, non-condensing				
Form Factor					
Touch Screen	5 Wires Resistive (Single touch)				
Mounting	VESA mount (100x100mm) & Yoke mount				
WIFI Optional	External Antenna (Wi-Fi): Supports M.2 Wi-Fi module with external antenna connection for enhanced signal performance				
Power adaptor	Full IP67 Waterproof Power adaptor : Specifications may vary by country (150W / 100 ~ 305V AC input / 12V DC output) / (150W / 100 ~ 305V AC input / 24V DC output)				

