


### 10.4" Open Frame Touch Monitor



#### Features

- Fanless and rugged design
- Wide temperature: -20°C ~ 60°C
- High brightness solution: 700 / 1000 / 1600nits
- 5W resistive / True flat PCT touch screen
- Resolution 1024 x 768 dpi
- Open frame mount

#### Specifications

| High Brightness            | 700nits                                                   |            | 1000nits | 1600nits  |
|----------------------------|-----------------------------------------------------------|------------|----------|-----------|
| DISPLAY                    |                                                           |            |          |           |
| Size                       | 10.4" TFT (4:3)                                           |            |          |           |
| Resolution                 | 1024 x 768                                                |            |          |           |
| Colors                     | 16.7M                                                     | 16.7M      |          | 16.7M     |
| Luminance                  | 700 cd/m2                                                 | 1000 cd/m2 |          | 700 cd/m2 |
| Contrast Ratio             | 900 : 1                                                   | 900 : 1    |          | 900 : 1   |
| Viewing Angle (H/V)        | 150°/150°                                                 | 150°/150°  |          | 150°/150° |
| POWER REQUIREMENT          |                                                           |            |          |           |
| Power Requirement          | DC in 12V                                                 |            |          |           |
| OS SUPPORT                 |                                                           |            |          |           |
| OS support                 | Win Pro 7.8.1, 10 / embedded Win 7, 8, 10                 |            |          |           |
| MECHANICAL & ENVIRONMENTAL |                                                           |            |          |           |
| Operation Temp.            | -20 ~ 60°C                                                |            |          |           |
| Storage Humidity           | 10 ~ 90%, non-condensing                                  |            |          |           |
| Mounting                   | Open frame mount                                          |            |          |           |
| Dimension (WxHxD)          | TBD                                                       |            |          |           |
| Weight                     | TBD                                                       |            |          |           |
| OPTIONAL                   |                                                           |            |          |           |
| P/N: 302A170052            | 700 cd/m2 High Brightness 10.4" LCD panel 1024 x 768 dpi  |            |          |           |
| P/N: 302A170054            | 1600 cd/m2 High Brightness 10.4" LCD panel 1024 x 768 dpi |            |          |           |
| P/N: 3080109001            | 2M DP cable                                               |            |          |           |
| P/N: 3080108001            | 2M HDMI cable                                             |            |          |           |
| P/N: 2320000001            | Optical bonding                                           |            |          |           |

| ORDERING INFORMATION |                                                                                                                                                                                          |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No.            | Products Description                                                                                                                                                                     |
| OM105RK03            | 10.4" wide temp fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2           |
| OM105PK03            | 10.4" wide temp fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2               |
| OM105EK03            | 10.4" wide temp fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2 |
| OM105RK04            | 10.4" wide temp fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2               |
| OM105PK04            | 10.4" open frame fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2                  |
| OM105EK04            | 10.4" open frame fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2    |

**\*\*If you select 700 cd/m2 or 1600 cd/m2 high brightness products, please change the model number and specifications in accordance with the rules of encoding.**