


15" Open Frame Touch Monitor



Features

- Fanless and rugged design
- Wide temperature: -20°C ~ 60°C
- High brightness solution: 700 / 1000 / 1600nits
- 5W resistive / True flat PCT touch screen
- Resolution 1024 x 768 dpi
- Open frame mount

Specifications

High Brightness	700nits		1000nits	1600nits
DISPLAY				
Size	15" TFT (4:3)			
Resolution	1024 x 768			
Colors	16.2M	16.2M		16.2M
Luminance	700 cd/m2	1000 cd/m2		1600 cd/m2
Contrast Ratio	2000 : 1	2000 : 1		2000 : 1
Viewing Angle (H/V)	176°/176°	176°/176°		176°/176°
POWER REQUIREMENT				
Power Requirement	DC in 12V			
OS SUPPORT				
OS support	Win Pro 7.8.1, 10 / embedded Win 7, 8, 10			
MECHANICAL & ENVIRONMENTAL				
Operation Temp.	-20 ~ 60°C			
Storage Humidity	10 ~ 90%, non-condensing			
Mounting	Open frame mount			
Dimension (WxHxD)	TBD			
Weight	TBD			
OPTIONAL				
P/N: 302A170054	700 cd/m2 High Brightness 15" LCD panel 1024 x 768 dpi			
P/N: 302A17005A	1600 cd/m2 High Brightness 15" LCD panel 1024 x 768 dpi			
P/N: 3080109001	2M DP cable			
P/N: 3080108001	2M HDMI cable			
P/N: 2320000001	Optical bonding			

ORDERING INFORMATION	
Model No.	Products Description
OM150RK03	15" wide temp fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
OM150PK03	15" wide temp fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
OM150EK03	15" wide temp fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
OM150RK04	15" wide temp fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
OM150PK04	15" wide temp fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
OM150EK04	15" wide temp fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2

****If you select 700 cd/m2 or 1600 cd/m2 high brightness products, please change the model number and specifications in accordance with the rules of encoding.**