


21.5" Open Frame Touch Monitor



Features

- Fanless and rugged design
- Wide temperature: -20°C ~ 60°C
- High brightness solution: 700 / 1000 / 1500nits
- 5W resistive / True flat PCT touch screen
- Resolution 1920 x 1080 dpi
- Open frame mount

Specifications

High Brightness	700nits	1000nits	1500nits
DISPLAY			
Size	21.5" TFT (16:9)		
Resolution	1920 x 1080		
Colors	16.2M	16.2M	16.7M
Luminance	700 cd/m2	1000 cd/m2	1500 cd/m2
Contrast Ratio	1000 : 1	1000 : 1	1000 : 1
Viewing Angle (H/V)	178°/178°	178°/178°	178°/178°
POWER REQUIREMENT			
Power Requirement	DC in 12V		
OS SUPPORT			
OS support	Win Pro 7.8.1, 10 / embedded Win 7, 8, 10		
MECHANICAL & ENVIRONMENTAL			
Operation Temp.	-20 ~ 60°C		
Storage Humidity	10 ~ 90%, non-condensing		
Mounting	Open frame mount		
Dimension (WxHxD)	TBD		
Weight	TBD		
OPTIONAL			
P/N: 302A170065	700 cd/m2 High Brightness 21.5" LCD panel 1920 x 1080 dpi		
P/N: 302A19009S	1500 cd/m2 High Brightness 21.5" LCD panel 1920 x 1080 dpi		
P/N: 3080109001	2M DP cable		
P/N: 3080108001	2M HDMI cable		
P/N: 2320000001	Optical bonding		

ORDERING INFORMATION	
Model No.	Products Description
OM215RK03	21.5" Wide temp. fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB , 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
OM215PK03	21.5" Wide temp. fanless open frame monitor, true flat PCT, 1 x VGA , 1 x DVI , 1 x USB , 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
OM215EK03	21.5" Wide temp. fanless open frame monitor, true flat 5 wires resistive, 1 x VGA , 1 x DVI , 1 x USB , 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
OM215RK04	21.5" Wide temp. fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
OM215PK04	21.5" Wide temp. fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
OM215EK04	21.5" Wide temp. fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2

****If you select 700 cd/m2 high brightness products, please change the model number and specifications in accordance with the rules of encoding.**